

LE1400







LEI400 SMART

THE TECHNOLOGY DELIVERS CONVENIENCE.

LEI400, automatic vending machine for hot drinks with 400 cups capacity. Designed to easily interchange the push-button panel and adapt to different locations.



LEI400 EASY + ARIA M MASTER

USER INTERFACE

• Great modularity with 2 interchangeable user interfaces:

Easy: standard membrane keypad, with 24 large buttons.

Smart: touchscreen saw technology selection panel (surface acoustic wave), with 24 wide backlighted selections.

- Customizable sugar dosage.
- End selection acoustic signal.
- 32 digit alphanumeric LCD displays.
- Slow falling product dispensing door.











SPECIFICATIONS

ELECTRICAL SUPPLY

230 Vac - 50 Hz / 120 Vac - 60 Hz

• INTERNAL ELECTRICAL SUPPLY

All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances, the pump and the steam ventilator that are at powered by the mains voltage.

• POWER SUPPLY

1.80 kW espresso version single boiler

2.25 kW instant version

WATER SUPPLY

Fitting connection = 3/4"

Water pressure = 0.5 - 6.5 bar

FEATURES

- Reinforced cabinet with anti-vandal hinges and door look with programmable code.
- Mixers and boiler assembly are extractable to make maintenance operations easier.
- Standard serpentine kit for tea on all versions.
- Cup dispenser adjustable to various diameters (from 70 to 74 mm) and dispenser for 90 or 105 mm stirrers.
- Switching power supply that guarantees total stability of the instant product dose and complete electric safety protections.
- Standard multi-protocol electronics.
- Compatible with telemetry.

PAYMENT SYSTEM

- Compatible with all payment systems available on the market.
- Can work in master/slave with only one set of payment system on the hot vending machine together with a refrigerated automatic spiral vending machine for the sale of snacks, cans and bottles, increasing selling opportunities.

PRODUCT CAPACITY

Coffee beans*	2.50 kg
Instant coffee	0.50 kg
Barley	0.60 kg
Powder milk	1.70 kg
Whitener	3.20 kg
Chocolate	3.60 kg
Lemon tea	3.30 kg
Tea	1.70 kg
Soup	3.60 kg
Sugar	4.00 kg
Spoons	400 pcs.
Cups	400 pcs.

^{*} With extension kit 3.80 kg.

ACCESSORIES KIT


- Cup sensor.
- Vandal-proof coin introduction.
- Kit clock chip (for energy saving mode and promotional activities).
- System for the automatic regulation of the coffee bean grinding that guarantees with the variations of the humidity and the emperature, the best quality of the product dispensed at all times.
- Additional canister and mixer to reach 7 canisters in the instant version.

ENVIRONMENT


- Backlighted lexan with led to reduce energy consumption and with a lifetime greater than neon.
- Compatible with paper cups and wooden spoons.
- Option: cup sensor to reduce the consumption of plastic cups and to deliver a beverage in a mug.
- Energy Saving Mode to reduce the energy cunsumption when the machine is in stand by.
- In compliance with ROHS and WEEE.

VERSIONS LEI400 EASY / SMART	ESPRESSO 1ES-6 SINGLE BOILER	INSTANT IN-6	
COFFEE BEAN	1	-	
INSTANT CANISTERS (SUGAR INCLUDED)	6	6	
DIMENSIONS MM	1630H x 620W x 744D / WEIGHT 132,5 KG		

1. Sugar 2. Instant 3. Instant 4. Coffee beans 5. Chocolate 6. Milk 7. Tea



1. Tea 2. Sugar 3. Coffee 4. Decaffeinated 5. Chocolate 6. Milk















MASTER/SLAVE

THE BEST VALUE FOR MONEY WHICH HARMONIZES WITH ELEGANCE WITH THE RANGE LEI.

ARIA M, automatic spiral refrigerated 3° C vending machine for the sale of snacks, confectionary, sandwiches, yogurts and other fresh perishable foodstuffs, cans and bottles; available in master or slave version.



USER INTERFACE

- Elegant design with the door frame in anodized aluminum.
- Wide product delivery area "push" for large products.
- Great versatility of configurations that allows multiple combinations, able to satisfy the different sales requests for a wide range of products.

SLAVE MODELS

- Slave version works together with a machine for hot drinks with a single payment system.
- Alphanumeric keyboard selection is on the hot drinks machine.

MASTER MODELS

- Stainless steel alphanumeric selection keypad with 12 push buttons.
- 32 digit graphic LCD display.
- Standard coin introduction system.



ARIA M MASTER

Bianchi Vending















SPECIFICATIONS

- ELECTRICAL SUPPLY: 230 Vac 50 Hz
- INTERNAL ELECTRICAL SUPPLY: 0.3 kW
- INTERNAL TEMPERATURE

Combi version: up to +8° C with ambient temperature of 32° C and 65% humidity.

Food version: preset for the preservation of perishable food products as equipped with refrigerator group that can guarantee 3° C in the two lower trays.

All 3° versions are equipped with health control safety device available on the last two trays and when the electronic sensor detect a temperature above the established safety temperature for perishable food products all food sales will be inhibited.

- COOLING UNIT
- 1/2 HP monobloc with automatic defrost control
- REFRIGERANT GAS:

R 134 A

FEATURES

- Slave models can be combined with 2 machines among hot beverage or snack & food with a sole payment system in the master version.
- Foamed vending machine to ensure complete isolation and avoid unnecessary losses of energy consumption.

- Large window display with led with double glazed glass that shows off the products to maximum advantage.
- Window with anti-condensation resistance.
- Adjustable tray height.
- Specific tray for triangular sandwiches on the food version.
- Door lock with programmable code.
- Anti-theft product delivery door.
- Products drop sensor.
- Standard multi-protocol electronics.
- Compatible with telemetry.

PAYMENT SYSTEM

• Only master models can accomodate all the main payment systems.

ACCESSORIES KIT

• Master models: sixth tray kit.

ENVIRONMENT

- Cold unit Class A+.
- Window lighting with LED.
- Energy Saving Mode: possibility to manage the options off Led lights at certain times.
- In compliance with ROHS and WEEE.

VERSIONS ARIA M	5-3X MA COMBI ALFA STD	5-3X MA FOOD ALFA STD	5-3X SL COMBI	5-3X SL FOOD
MODEL	MASTER	MASTER	SLAVE	SLAVE
SELECTIONS/CAPACITY	27/271	26/229	36/292	35/279
TRAYS/SPIRALS	5/6	5/6	5/8	5/8
DIMENSION MM	MASTER AND SLAVE VERSIONS: 1630H x 700W x 807D			

